

Mold No.	J1	062,063


REVISIONS			
REV.	DESCRIPTION	DATE	REVISED BY
S0	CREATED DRAWING	10/12/26	Ruby_zhang





DETAIL A

LABEL DETAIL A NOTE:
1.Material:Art paper.
2.Black texts with white background.
3.Text Height 3.0mm Max,Font"Arial"



Electrical Character
Rating voltage: 300V AC/DC
Insulation resistance: >100MΩ
Rating current: 4A
Contact resistance: ≤5mΩ
Ambient Temperature: −40°C~+125°C
ALL MATERIALS ARE COMPLIANT WITH ROHS OR REACH

Electrical Performance:
1.100%TESTED FOR OPENS SHORTS
2.INSULATION RESISTANCE: 5M ohm
3.CONNECTING RESISTANCE: 5 ohm
4.HI−POT:DC 300V 10ms

Pin Out

J1	COLOR	J2
1	RED	OPEN
2	BLACK	

No.	Part No.	DESCRIPTION	Q'TY	UNIT
⑥	--	30P RED PVC −40°C~+125°C	15	g
⑤	--	LD PE	10	g
④	--	AMPHENOL P/N:AW2S	1	PC
③	--	AMPHENOL P/N:AT62−16−0122	2	PCS
②	--	AMPHENOL P/N:AT06−2S	1	PC
①	CB1214	18AWG*1P+F JACKET BLACK XL PE CABLE OD=5.0mm −40°C~+125°C 300V	AR	M

FormRep

DRAWN BY: JiXiang_Huang	DATE: 10/12/26	
CHECKED BY: Ruby_zhang	DATE: 10/12/26	
APPROVED BY: David	DATE: 10/12/26	

TITLE: AMPHENOL 2P cable

Customer Part No:	REV.	--	UNITS: mm
Part No: 3443	REV.	S0	SCALE: NONE

Tolerances Unless Otherwise Specified:
DECIMALES: X. ±0.30 .X ±0.20
ANGLES: X°. ±2.0° .X° ±1.0°

PROJECTION:

SIZE: A4

SHEET: 1 OF 1