

M12 L-Coded Female Straight Molded Cable, Single-Ended

M12 × 1.0 L-coded 4/5-pin female straight connector, overmolded onto PUR or PVC cable for DC power. 1, 2, 5 or 10 m.



ORDERING CODE

M12L-[4/5]P-F-ST-[jacket]-[U/S]-[length]M

CONNECTOR

M12 × 1.0, L-coded, female, straight

PINS AND CODING

4/5-pin L-coded · DC power

CABLE

PUR or PVC jacket · unshielded or shielded

LENGTHS

1 m, 2 m, 5 m, 10 m

CABLE TEMPERATURE

−40 to +105 °C

CONSTRUCTION

Standard	IEC 61076-2-101
Connector	M12 × 1.0, L-coded, female, straight
Termination	Soldered and overmolded
Contacts	Brass, gold plated
Coupling	Screw lock, brass, nickel plated
Overmold	TPU body and overmold
Shield (S)	Brass shell, nickel plated
Jacket	PUR or PVC, black, −40 to +105 °C
Wire gauge	Conductor size set by current; confirm at quote
Free end	Open conductors

RATINGS

4-pin L-coded	12 A · voltage per quote
5-pin L-coded	12 A · voltage per quote

GENERAL

Current rating at	40 °C
Cable temp.	−40 to +105 °C
Insulation resist.	≥ 100 MΩ
Contact resist.	≤ 5 mΩ
Mating cycles	> 100
Compliance	RoHS / REACH


BUILT TO ORDER

Standard configurations ship in about 5 to 6 weeks. Request a quote on formrep.com or call 816-782-7800.

NEED SOMETHING DIFFERENT?


Other lengths, cable types and mixed-connector versions are available. Ask for a made-to-fit quote.

Dimensions, pin layouts and ordering




PIN LAYOUTS, FEMALE FACE VIEW (MATING SIDE)

4-pin L-coded



Female face view (mating side)

5-pin L-coded



Female face view (mating side)

ORDERING CODE

M12L

M12 L-coded

4P

4/5 pins

F-ST

this cable family

PUR

jacket: PUR or PVC

U

U = unshielded, S = shielded

2M

length: 1M, 2M, 5M, 10M

Example: M12L-4P-F-ST-PUR-U-2M = 4-pin L-coded M12 female straight, PUR jacket, unshielded, 2 m.

STANDARD CONFIGURATIONS (32)

M12L-4P-F-ST-PUR-U-1M	M12L-4P-F-ST-PUR-S-5M	M12L-4P-F-ST-PVC-S-1M	M12L-5P-F-ST-PUR-U-5M	M12L-5P-F-ST-PVC-U-1M	M12L-5P-F-ST-PVC-S-5M
M12L-4P-F-ST-PUR-U-2M	M12L-4P-F-ST-PUR-S-10M	M12L-4P-F-ST-PVC-S-2M	M12L-5P-F-ST-PUR-U-10M	M12L-5P-F-ST-PVC-U-2M	M12L-5P-F-ST-PVC-S-10M
M12L-4P-F-ST-PUR-U-5M	M12L-4P-F-ST-PVC-U-1M	M12L-4P-F-ST-PVC-S-5M	M12L-5P-F-ST-PUR-S-1M	M12L-5P-F-ST-PVC-U-5M	
M12L-4P-F-ST-PUR-U-10M	M12L-4P-F-ST-PVC-U-2M	M12L-4P-F-ST-PVC-S-10M	M12L-5P-F-ST-PUR-S-2M	M12L-5P-F-ST-PVC-U-10M	
M12L-4P-F-ST-PUR-S-1M	M12L-4P-F-ST-PVC-U-5M	M12L-5P-F-ST-PUR-U-1M	M12L-5P-F-ST-PUR-S-5M	M12L-5P-F-ST-PVC-S-1M	
M12L-4P-F-ST-PUR-S-2M	M12L-4P-F-ST-PVC-U-10M	M12L-5P-F-ST-PUR-U-2M	M12L-5P-F-ST-PUR-S-10M	M12L-5P-F-ST-PVC-S-2M	