

M12 S-Coded Male to Male Right-Angle Cable

M12 × 1.0 S-coded 4-pin, male right-angle to male right-angle, overmolded both ends, for AC power. 1, 2, 5 or 10 m.



ORDERING CODE

M12S-4P-MM-RA-[jacket]-[U/S]-[length]M

CONNECTOR

M12 × 1.0, S-coded, male, right-angle to male right-angle

PINS AND CODING

4-pin S-coded · AC power

CABLE

PUR or PVC jacket · unshielded or shielded

LENGTHS

1 m, 2 m, 5 m, 10 m

CABLE TEMPERATURE

−40 to +105 °C

CONSTRUCTION

Standard	IEC 61076-2-101
Connector	M12 × 1.0, S-coded, male, right-angle to male right-angle
Termination	Soldered and overmolded
Contacts	Brass, gold plated
Coupling	Screw lock, brass, nickel plated
Overmold	TPU body and overmold
Shield (S)	Brass shell, nickel plated
Jacket	PUR or PVC, black, −40 to +105 °C
Wire gauge	Conductor size set by current; confirm at quote
Wiring	Straight through, pin to pin

RATINGS

4-pin S-coded	630 V · 12 A
---------------	--------------

GENERAL

Current rating at	40 °C
Cable temp.	−40 to +105 °C
Insulation resist.	≥ 100 MΩ
Contact resist.	≤ 5 mΩ
Mating cycles	> 100
Compliance	RoHS / REACH


BUILT TO ORDER

Standard configurations ship in about 5 to 6 weeks. Request a quote on formrep.com or call 816-782-7800.

NEED SOMETHING DIFFERENT?

Other lengths, cable types and mixed-connector versions are available. Ask for a made-to-fit quote.

Dimensions, pin layouts and ordering



PIN LAYOUT, MALE FACE VIEW, BOTH ENDS (MATING SIDE)

4-pin S-coded



Male face view (mating side)

ORDERING CODE

M12S	-	4P	-	MM-RA	-	PUR	-	U	-	2M
M12 S-coded		4 pins		this cable family		jacket: PUR or PVC		U = unshielded, S = shielded		length: 1M, 2M, 5M, 10M

Example: M12S-4P-MM-RA-PUR-U-2M = 4-pin S-coded M12 male right-angle to male right-angle, PUR jacket, unshielded, 2 m.

STANDARD CONFIGURATIONS (16)

M12S-4P-MM-RA-PUR-U-1M	M12S-4P-MM-RA-PUR-U-10M	M12S-4P-MM-RA-PUR-S-5M	M12S-4P-MM-RA-PVC-U-2M	M12S-4P-MM-RA-PVC-S-1M	M12S-4P-MM-RA-PVC-S-10M
M12S-4P-MM-RA-PUR-U-2M	M12S-4P-MM-RA-PUR-S-1M	M12S-4P-MM-RA-PUR-S-10M	M12S-4P-MM-RA-PVC-U-5M	M12S-4P-MM-RA-PVC-S-2M	
M12S-4P-MM-RA-PUR-U-5M	M12S-4P-MM-RA-PUR-S-2M	M12S-4P-MM-RA-PVC-U-1M	M12S-4P-MM-RA-PVC-U-10M	M12S-4P-MM-RA-PVC-S-5M	