

M12 S-Coded Panel-Mount Receptacle, PCB Pins

M12 × 1.0 S-coded panel-mount receptacle with PCB pins. Male or female; straight front or rear mount, or right-angle front mount. 4 pins. For AC power.



ORDERING CODE

M12S-4P-[M/F]-[ST/RA]-[FR/RR]-PCB-[PG9/M16/M12]

CONNECTOR

M12 × 1.0, S-coded, male or female

MOUNTING

Straight front or rear mount, or right-angle front mount

PINS

4

PANEL THREAD

PG9 or M16 or M12 (see notes)

TERMINATION

PCB pins

CONSTRUCTION

Standard	IEC 61076-2-101
Termination	PCB pins
Locking	M12 × 1.0 screw
Contacts	Brass, gold plated
Nut and shell	Brass, nickel plated
Insert	TPU
Seal	FKM

RATINGS

4-pin S-coded	630 V · 12 A
---------------	--------------

GENERAL

Operating temp.	–25 to +85 °C
Current rating at	40 °C
Insulation resist.	≥ 100 MΩ
Contact resist.	≤ 5 mΩ
Mating cycles	> 100
Compliance	RoHS / REACH


BUILT TO ORDER

Standard versions ship in about 5 to 6 weeks. Request a quote on formrep.com or call 816-782-7800.


NEED SOMETHING DIFFERENT?

Other lead lengths, threads and codings may be available. Ask for a made-to-fit quote.


Dimensions, pin layouts and ordering




MALE, STRAIGHT, FRONT MOUNT




FEMALE, STRAIGHT, FRONT MOUNT



MALE, STRAIGHT, REAR MOUNT




FEMALE, STRAIGHT, REAR MOUNT



FEMALE, RIGHT-ANGLE, FRONT MOUNT

PIN LAYOUTS, FACE VIEW (MATING SIDE); MALE TOP ROW, FEMALE BOTTOM ROW



ORDERING CODE

M12S	-	4P	-	M	-	ST	-	FR	-	PCB	-	PG9
M12 S-coded		pins: 4		M = male, F = female		ST or RA head		FR = front, RR = rear mount		PCB pins		PG9/M16/M12 thread

Example: M12S-4P-M-ST-FR-PCB-PG9 = 4-pin S-coded male straight, front mount receptacle, PCB pins, PG9 thread.

STANDARD CONFIGURATIONS (9)

M12S-4P-M-ST-FR-PCB-PG9	M12S-4P-F-ST-FR-PCB-M16	M12S-4P-F-ST-RR-PCB-PG9
M12S-4P-M-ST-FR-PCB-M16	M12S-4P-M-ST-RR-PCB-PG9	M12S-4P-F-ST-RR-PCB-M16
M12S-4P-F-ST-FR-PCB-PG9	M12S-4P-M-ST-RR-PCB-M16	M12S-4P-F-RA-FR-PCB-M12