

M12 X-Coded Male Right-Angle Molded Cable, Single-Ended

M12 × 1.0 X-coded 8-pin male right-angle connector, overmolded onto PUR or PVC cable for industrial Ethernet. 1, 2, 5 or 10 m.



ORDERING CODE

M12X-8P-M-RA-[jacket]-S-[length]M

CONNECTOR

M12 × 1.0, X-coded, male, right-angle

PINS AND CODING

8-pin X-coded · industrial Ethernet

CABLE

PUR or PVC jacket · shielded

LENGTHS

1 m, 2 m, 5 m, 10 m

CABLE TEMPERATURE

–40 to +105 °C

CONSTRUCTION

Standard	IEC 61076-2-101
Connector	M12 × 1.0, X-coded, male, right-angle
Termination	Soldered and overmolded
Contacts	Brass, gold plated
Coupling	Screw lock, brass, nickel plated
Overmold	TPU body and overmold
Shield (S)	Brass shell, nickel plated
Jacket	PUR or PVC, black, –40 to +105 °C
Wire gauge	0.14 mm ² (26 AWG)
Free end	Open conductors

RATINGS

8-pin X-coded	60 V · 0.5 A
---------------	--------------

GENERAL

Current rating at	40 °C
Cable temp.	–40 to +105 °C
Insulation resist.	≥ 100 MΩ
Contact resist.	≤ 5 mΩ
Mating cycles	> 100
Compliance	RoHS / REACH


BUILT TO ORDER

Standard configurations ship in about 5 to 6 weeks. Request a quote on formrep.com or call 816-782-7800.

NEED SOMETHING DIFFERENT?


Other lengths, cable types and RJ45 or mixed-connector versions are available. Ask for a made-to-fit quote.

Dimensions, pin layouts and ordering



PIN LAYOUTS, MALE FACE VIEW (MATING SIDE)

8-pin X-coded



Male face view (mating side)

ORDERING CODE

M12X

M12 X-coded

8P

8 pins

M-RA

this cable family

PUR

jacket: PUR or PVC

S

S = shielded

2M

length: 1M, 2M, 5M, 10M

Example: M12X-8P-M-RA-PUR-S-2M = 8-pin X-coded M12 male right-angle, PUR jacket, shielded, 2 m.

STANDARD CONFIGURATIONS (8)

M12X-8P-M-RA-PUR-S-1M
M12X-8P-M-RA-PUR-S-2M
M12X-8P-M-RA-PUR-S-5M
M12X-8P-M-RA-PUR-S-10M
M12X-8P-M-RA-PVC-S-1M
M12X-8P-M-RA-PVC-S-2M
M12X-8P-M-RA-PVC-S-5M
M12X-8P-M-RA-PVC-S-10M